HAVOLINE® POWER STEERING FLUID

PRODUCT DESCRIPTION

Fluid for automotive power steering systems in automobiles and light trucks.

CUSTOMER BENEFITS

Havoline® Power Steering Fluid delivers value through:

- **Protection against pump wear**
- **Protection against deterioration of seals and hoses**
- **Protection against corrosion, rust, and oxidation**

FEATURES

Havoline Power Steering Fluid is a general purpose power steering fluid.

Havoline Power Steering Fluid is blended with high quality base stocks and a balanced additive system containing friction modifiers, anti-wear agents, and inhibitors against oxidation, foam, and rust.

APPLICATIONS

Havoline Power Steering Fluid can be used in power steering applications where DEXRON®, DEXRON®-II, DEXRON®-II D, DEXRON®-III or MERCON® is required.[1] Check owner's manual for correct fluid type recommended.

Havoline Power Steering Fluid is recommended for automotive power steering systems in automobiles and light trucks. It is not recommended for use in Honda vehicles.

It is designed for use in applications which call for the following OEM specifications:

OEM	Specification
Audi/VW	VW TL 570-26 (P/N: ZVW 239-902)
FCA	Chrysler MS-1872
	Chrysler MS-5931 (P/N: 04883077)
	Chrysler MS-9602 (ATF+4)
Ford	Ford M2C128-C&D
	Ford M2C138-CJ
	Ford M2C195-A
	Ford M2C33-F
	Ford MS-5931
General Motors	GM 1050017
	GM 19329450
	GM 89021184
	GM 89021885 (US)
	GM 89021186 (CAN)
	GM 9985010
	GM IID
	GM III
Hyundai/Kia	Hyundai/Kia PSF-3
Mercedes Benz	MB 236.3 (P/N: 000 989 88 03)
Mitsubishi	Mitsubishi Dia Queen PSF
	Mitsubishi SP-III
Nissan	Nissan PSF-II
Saab	Saab 30 09 800
Subaru	Subaru K0209A0080
Toyota	Toyota PSF Type EH (P/N: 08886-01206)

1 DEXRON is a registered trademark of General Motors Corporation.
MERCON is a registered trademark of Ford Motor Company.

Product(s) manufactured in the USA.
Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 September 2026
GL-35

© 2007-2026 Chevron U.S.A. Inc. All rights reserved.
Chevron, the Chevron Hallmark and Havoline are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

TYPICAL TEST DATA

	Test Method	
Product Number		*221806*
SDS Number		*10825*
API Gravity	ASTM D4052	33.85
Viscosity, Kinematic cSt at 40°C cSt at 100°C	ASTM D445	 32.8 7.1
Viscosity, Brookfield cP at -40°C	ASTM D2983 (mod)	 20,000
Viscosity Index	ASTM D2270	185
Flash Point, °C(°F)	ASTM D92	205(401)
Pour Point, °C(°F)	ASTM D97	-51(-60)
Color		Red

Minor variations in product typical test data are to be expected in normal manufacturing.

CONTACT INFORMATION

You can contact Chevron Global Lubricants in the United States in several ways, depending on your question or requirement, please review the following options:

Chevron Headquarters

Chevron Corporation (Corporate Offices)
1400 Smith Street
Houston, TX 77002
United States

General Questions and Feedback

Chevron Information Center: 1-800-533-6571

USA Customer Service: 1-800-526-3013

LUBETEK technical staff: lubetek@chevron.com

To locate the Chevron Lubrication Marketer or agent nearest you, visit www.chevronlubricants.com, select an industry and click on "Marketer Locator" or call 1-800-822-5823.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.