Delo[®] Silver Multigrade

Heavy-Duty Diesel Engine Oil



Product description

Delo[®] Silver Multigrade is a multigrade heavy-duty diesel engine oil designed to lubricate engines requiring API CF-4, CF / SG performance lubricants.

Customer benefits

• Saves on maintenance

Metallic detergent and ashless dispersant additive system provides high temperature deposit control in diesel engines. High oxidation stability protects against the formation of gums and varnish at elevated temperatures, and resists thickening, and oil line and filter plugging.

• Longer engine life

Proven metallo-organic anti-wear additive system protects against wear of critically loaded components under all operating conditions. Multigrade viscosity provides additional protection against wear at start-up and under high temperature operating conditions.

• Preserves power and performance

Metallic detergent and ashless dispersant additive system maintains power and performance by providing good upper-ring-belt deposit control, particularly under the high temperatures encountered in turbocharged diesel engines.

Applications

- Mixed fleets of diesel engines (high-speed, four-stroke, turbocharged or naturally aspirated)
- Gasoline engines (four-stroke) in mixed fleets of both diesel and gasoline engines
- Commercial road transport
- Off-highway vehicles
- Agricultural tractors
- High speed diesel engines in marine service (e.g., fishing boats, river transport)
- Generator sets
- Mobile hydraulic systems (where oil type and viscosity are appropriate)

Product approvals, performance and recommendations

Meets the Requirements of

• API CF-4, CF / SG

Delo[®] Silver Multigrade

Heavy-Duty Diesel Engine Oil



Typical test data

| DELO [®] SILVER MULTIGRADE | RESULTS | | |
|-------------------------------------|---------|--------|--------|
| SAE Grade | 10W-30 | 15W-40 | 20W-50 |
| Product Code | 500548 | 500549 | 500551 |
| Base No., D2896, mg KOH/g | 10.3 | 10.3 | 10.3 |
| Base No., D4739, mg KOH/g | 9.3 | 9.3 | 9.3 |
| Sulfated Ash, m % | 1.2 | 1.2 | 1.2 |
| Viscosity, mm²/s @ 100°C | 12.0 | 15.2 | 19.1 |
| Viscosity Index | 140 | 130 | 125 |
| Zinc, m % | 0.14 | 0.14 | 0.14 |

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Asia-Pacific region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

