Safety Data Sheet



SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

HDAX 9200 Low Ash Gas Engine Oil SAE 40

Product Number(s): 803231

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: Stationary Gas Engine Oil

1.3 Details of the supplier of the safety data sheet

Chevron Products UK Limited 1 Westferry Circus Canary Wharf London E14 4HA United Kingdom

email: eumsds@chevron.com

1.4 Emergency telephone number

Transportation Emergency Response

Europe: 0044/(0)18 65 407333 and CHEMTREC: +1 703 527 3887

Health Emergency

Chevron Emergency Information Center: Located in the USA, international calls accepted 24 hours: +1

510 231 0623

Europe: 0044/(0)18 65 407333

Product Information

Product Information: FAX number: 0044/20 77 19 5171

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLP CLASSIFICATION:

Not classified as dangerous according to UK REACH regulation.

2.2 Label elements

Under the criteria of GB CLP:

Not classified

- contains: Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide,

distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts. May produce an allergic reaction. Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium

salts. May produce an allergic reaction.

Revision Number: 7
Revision Date: October 28, 2024

HDAX 9200 Low Ash Gas Engine Oil SAE 40

2.3 Other hazards

This material does not contain a substance considered to have endocrine disrupting properties at levels of 0.1% weight or higher. This material does not contain a substance considered to be PBT or vPvB at levels of 0.1% weight or higher.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

This material is a mixture.

COMPONENTS	CAS NUMBER	EC NUMBER	REGISTRATION NUMBER	GB CLP CLASSIFICATION	AMOUNT
Highly refined mineral oil (C15 - C50)	Mixture	*	**	None	70 - 99 %weight
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propiona te	125643-61-0	406-040-9	**	Aquatic Chronic 4/H413	1 - 5 %weight
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	68855-45-8	701-249-4	UK-01- 2548210003-6	Aquatic Chronic 4/H413	1 - 5 %weight
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Not Applicable	944-406-4	**	Aquatic Chronic 3/H412; Skin Sens. 1/H317; Skin Irrit. 2/H315 [C>=9.83]	0.1 - < 1 %weight
Benzenesulfonic acid, methyl-, mono-C20-24- branched alkyl derivs., calcium salts	722503-68-6	682-816-2	**	Skin Sens. 1B/H317	0.1 - < 1 %weight

The full text of all CLP H-statements is shown in Section 16.

In accordance with reference IP 346/92: "DMSO Extraction Method", we have determined that the base oils used in this preparation contain <3% DMSO extract and are not carcinogenic.

*Contains one or more of the following EINECS numbers: 265-090-8, 265-091-3, 265-096-0, 265-097-6, 265-098-1, 265-101-6, 265-155-0, 265-156-6, 265-157-1, 265-158-7, 265-159-2, 265-160-8, 265-166-0, 265-169-7, 265-176-5, 276-736-3, 276-737-9, 276-738-4, 278-012-2.

HDAX 9200 Low Ash Gas Engine Oil SAE 40

Revision Date: October 28, 2024

Revision Number: 7

^{**}Not available or substance is not currently required for registration under UK REACH.

SECTION 4 FIRST AID MEASURES

4.1 Description of first aid measures

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

4.2 Most important symptoms and effects, both acute and delayed IMMEDIATE SYMPTOMS AND HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin is not expected to be harmful.

Ingestion: Not expected to be harmful if swallowed.

Inhalation: Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

DELAYED OR OTHER SYMPTOMS AND HEALTH EFFECTS: Not classified.

4.3 Indication of any immediate medical attention and special treatment needed Not applicable.

SECTION 5 FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

5.2 Special hazards arising from the substance or mixture

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Calcium, Nitrogen, Sulfur

5.3 Advice for firefighters

This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Observe all relevant local and international regulations. Eliminate all sources of ignition in vicinity of spilled material. Keep out unnecessary and unprotected personnel. Persons entering the contaminated area to correct the problem or to determine whether it is safe to resume normal activities must comply with all instructions in the Exposure Controls/PersonalProtection section. Refer to Sections 5 and 8 for more information.

Revision Number: 7
Revision Date: October 28, 2024

HDAX 9200 Low Ash Gas Engine Oil SAE 40

6.2 Environmental precautions

Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater.

6.3 Methods and material for containment and cleaning up

Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil and dispose of in a manner consistent with applicable requirements. Place other contaminated materials in disposable containers and dispose of in a manner consistent with applicable requirements. Report spills to local authorities as appropriate or required.

6.4 Reference to other sections

See sections 8 and 13.

SECTION 7 HANDLING AND STORAGE

7.1 Precautions for safe handling

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

7.2 Conditions for safe storage, including any incompatibilities Not Applicable

7.3 Specific end use(s): Stationary Gas Engine Oil

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

8.1 Control parameters **Occupational Exposure Limits:**

Revision Number: 7 4 of 15 HDAX 9200 Low Ash Gas Engine Oil Revision Date: October 28, 2024 SAE 40

gency			Ğ	Notation
ilited	 5 mg/m3	10 mg/m3	-	
n	 ited	ited 5 mg/m3	ited 5 mg/m3 10 mg/m3	ited 5 mg/m3 10 mg/m3

Consult local authorities for appropriate values.

8.2 Exposure controls **ENGINEERING CONTROLS:**

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

Skin Protection: Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and complete facial protection. Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced. Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

Chemical Glove Material	Thickness (mm)	Typical Breakthrough Time (minutes)
Butyl	0.7	120
Nitrile	0.8	240
Viton Butyl	0.3	240

Respiratory Protection: A site-specific risk assessment should be conducted by an Occupational Hygienist or a Safety Professional to determine the type and use of respiratory protective equipment. When a site-specific risk assessment determines that respiratory protection is required, use an approved respirator such as:

Air purifying respirator -

If airborne concentration limits exceed the applicable occupational exposure limit, but are below the maximum use concentration.

Vapors only: organic vapor cartridge (filter type A3 per EN 529:2005).

Vapors and particulates (including generated mists): both an organic vapor cartridge & particulate filter (AP3 filter per EN 529:2005).

Refer to respirator manufacturers to obtain service life of cartridge / filter.

Positive pressure air-supplying respirator -

If airborne concentration limits exceed the maximum use concentration offered from an air purifying respirator.

Refer to EN 529:2005, USA OSHA 1910.134, and/or other applicable local/regional/national/international standards for regulatory requirements.

ENVIRONMENTAL EXPOSURE CONTROLS:

See relevant Community environmental protection legislation or the Annex, as applicable.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Revision Number: 7 5 of 15 HDAX 9200 Low Ash Gas Engine Oil Revision Date: October 28, 2024 **SAE 40**

9.1 Information on basic physical and chemical properties

Appearance

Color: Brown to yellow Physical State: Liquid **Odor:** Petroleum odor

Odor Threshold: No data available

pH: Not Applicable

Melting Point: No data available Freezing Point: No data available Initial Boiling Point: No data available

Flashpoint: (Cleveland Open Cup) 230 °C (446 °F) (Minimum)

Evaporation Rate: No data available Flammability (solid, gas): Not Applicable

Flammability (Explosive) Limits (% by volume in air): Lower: Not Applicable Upper: Not Applicable

Vapor Pressure: No data available Relative Vapor Density: No data available **Density:** 0.881 kg/l @ 15°C (59°F) (Typical)

Solubility: Soluble in hydrocarbons; insoluble in water

Partition coefficient n-octanol/water (logarithmic value): No data available

Auto-ignition temperature: No data available **Decomposition temperature:** No data available

Kinematic Viscosity: 125.1 mm2/s @ 40°C (104°F) (Typical)

Explosive Properties: No Data Available Oxidising properties: No Data Available

9.2 Other Information: No Data Available

SECTION 10 STABILITY AND REACTIVITY

10.1 Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

10.2 Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions: Hazardous polymerization will not occur.

10.4 Conditions to Avoid: Not applicable

10.5 Incompatible materials to avoid: Not applicable

10.6 Hazardous decomposition products: None known (None expected)

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes

Product Information:

Serious Eye Damage/Irritation: The material is not considered an eye irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Skin Corrosion/Irritation: The material is not considered a skin irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Skin Sensitization: The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Dermal Toxicity: The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Revision Number: 7 6 of 15 HDAX 9200 Low Ash Gas Engine Oil SAE 40 Revision Date: October 28, 2024

Acute Toxicity Estimate (dermal): Not Applicable

Acute Oral Toxicity: The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Toxicity Estimate (oral): Not Applicable

Acute Inhalation Toxicity: The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Toxicity Estimate (inhalation): Not Applicable

Germ Cell Mutagenicity: The material is not considered a mutagen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Carcinogenicity: The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Reproductive Toxicity: The material is not considered a reproductive toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Single Exposure: The material is not considered a target organ toxicant (single exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Repeated Exposure: The material is not considered a target organ toxicant (repeated exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Aspiration Hazard: The material is not considered an aspiration hazard.

Component Information:

Serious Eye Damage/Irritation:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9- alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Based on available data, the classification criteria are not met

Skin Corrosion/Irritation:		
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met	
Phenol, paraalkylation products with	Based on available data, the classification criteria are not met	

Revision Number: 7
Revision Date: October 28, 2024

HDAX 9200 Low Ash Gas Engine Oil SAE 40

C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	
Reaction mass of isomers of: C7-9- alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Test Result: Causes skin irritation

Skin Sensitization:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9- alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Test Result: May cause allergic skin reaction * read-across data from similar material
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Protocol: OECD 406 - Skin Sensitization Test Result: May cause allergic skin reaction * read-across data from similar material

Acute Dermal Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9- alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide,	Based on available data, the classification criteria are not met

Revision Number: 7 8 of 15 HDAX 9200 Low Ash 6 SAE 40

distn. residues from manuf. of phenol	
(tetrapropenyl) derivs. and phenol	
(tetrapropenyl) derivs., calcium salts	

Acute Oral Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9- alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Based on available data, the classification criteria are not met

Acute Inhalation Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9- alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Based on available data, the classification criteria are not met

Germ Cell Mutagenicity:		
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met	
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met	
Reaction mass of isomers of: C7-9-alkyl	Based on available data, the classification criteria are not met	

Revision Number: 7 Revision Date: October 28, 2024 HDAX 9200 Low Ash Gas Engine Oil SAE 40 SDS: 37732

3-(3,5-di-tert-butyl-4-	
hydroxyphenyl)propionate	
Benzenesulfonic acid, methyl-, mono-	Based on available data, the classification criteria are not met
C20-24-branched alkyl derivs., calcium	
salts	
Phenol, 2(or 4)-C20-24-alkyl derivs.,	Based on available data, the classification criteria are not met
reaction products with carbon dioxide,	
distn. residues from manuf. of phenol	
(tetrapropenyl) derivs. and phenol	
(tetrapropenyl) derivs., calcium salts	

Carcinogenicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9- alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Based on available data, the classification criteria are not met

Reproductive Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9- alkyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Based on available data, the classification criteria are not met

Specific Target Organ Toxicity - Single Exposure:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with	Based on available data, the classification criteria are not met

HDAX 9200 Low Ash Gas Engine Oil SAE 40 SDS: 37732 10 of 15 Revision Number: 7 Revision Date: October 28, 2024

C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Based on available data, the classification criteria are not met

Specific Target Organ Toxicity - Repeated Exposure:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, calcium salts, sulfurized including distillates (petroleum), hydrotreated, solvent-refined/dewaxed,cat. dewaxed, light/heavy paraffinic C15-C50†	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Phenol, 2(or 4)-C20-24-alkyl derivs., reaction products with carbon dioxide, distn. residues from manuf. of phenol (tetrapropenyl) derivs. and phenol (tetrapropenyl) derivs., calcium salts	Based on available data, the classification criteria are not met

ADDITIONAL TOXICOLOGY INFORMATION:

During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

11.2 Information on other hazards

No other hazards identified.

SECTION 12 ECOLOGICAL INFORMATION

Product Information:

12.1 Toxicity

This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

12.2 Persistence and degradability

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

Revision Number: 7 11 of 15 HDAX 9200 Low Ash Gas Engine Oil Revision Date: October 28, 2024 SAE 40

12.3 Bioaccumulative potential

Bioconcentration Factor: No Data Available

Partition coefficient n-octanol/water (logarithmic value): No data available

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

This material does not meet the criteria for PBT or vPvB.

12.6 Endocrine Disrupting Properties

This mixture does not contain any substances that are assessed as having endocrine disrupting properties.

12.7 Other adverse effects

No other adverse effects identified.

Component Information:

Component information.	
Acute Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phenol, paraalkylation products with C10-	No test data available
15 branched olefins (C12 rich) derived	
from propene oligomerization, calcium	
salts, sulfurized including distillates	
(petroleum), hydrotreated, solvent-	
refined/dewaxed,cat. dewaxed,	
light/heavy paraffinic C15-C50†	
Reaction mass of isomers of: C7-9-alkyl	Protocol: OECD 202-Daphnia Immob/Repro
3-(3,5-di-tert-butyl-4-	Test Qualifier: EC50
hydroxyphenyl)propionate	Test Result: >100 mg/l
	Species: Invertebrate
	Duration:24 hour(s)
Benzenesulfonic acid, methyl-, mono-	Based on available data, the classification criteria are not met
C20-24-branched alkyl derivs., calcium	
salts	
Phenol, 2(or 4)-C20-24-alkyl derivs.,	Protocol: OECD 201-Alga Growth Inhib
reaction products with carbon dioxide,	Test Qualifier: ELR50 (growth rate)
distn. residues from manuf. of phenol	Test Result: 36 mg/l (WAF)
(tetrapropenyl) derivs. and phenol	Species: Algae
(tetrapropenyl) derivs., calcium salts	Duration:72 hour(s)
Phenol, 2(or 4)-C20-24-alkyl derivs.,	Protocol: OECD 202-Daphnia Immob/Repro
reaction products with carbon dioxide,	Test Qualifier: EC50
distn. residues from manuf. of phenol	Test Result: 17 mg/l (WAF)
(tetrapropenyl) derivs. and phenol	Species: Invertebrate
(tetrapropenyl) derivs., calcium salts	Duration:48 hour(s)

Long-term Toxicity:		
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met	
Phenol, paraalkylation products with C10-	No test data available	
15 branched olefins (C12 rich) derived		
from propene oligomerization, calcium		
salts, sulfurized including distillates		
(petroleum), hydrotreated, solvent-		
refined/dewaxed,cat. dewaxed,		
light/heavy paraffinic C15-C50†		
Reaction mass of isomers of: C7-9-alkyl	No test data available	
3-(3,5-di-tert-butyl-4-		

12 of 15

Revision Number: 7 Revision Date: October 28, 2024 HDAX 9200 Low Ash Gas Engine Oil

hydroxyphenyl)propionate	
Benzenesulfonic acid, methyl-, mono-	Based on available data, the classification criteria are not met
C20-24-branched alkyl derivs., calcium	
salts	
Phenol, 2(or 4)-C20-24-alkyl derivs.,	No test data available
reaction products with carbon dioxide,	
distn. residues from manuf. of phenol	
(tetrapropenyl) derivs. and phenol	
(tetrapropenyl) derivs., calcium salts	

Biodegradation:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9-alkyl	Protocol: OECD 301B-Modified Sturm
3-(3,5-di-tert-butyl-4-	Test Result: Not readily biodegradable
hydroxyphenyl)propionate	
Phenol, paraalkylation products with C10-	Not applicable
15 branched olefins (C12 rich) derived	
from propene oligomerization, calcium	
salts, sulfurized including distillates	
(petroleum), hydrotreated, solvent-	
refined/dewaxed,cat. dewaxed,	
light/heavy paraffinic C15-C50†	
Phenol, 2(or 4)-C20-24-alkyl derivs.,	Test Result: Not readily biodegradable
reaction products with carbon dioxide,	
distn. residues from manuf. of phenol	
(tetrapropenyl) derivs. and phenol	
(tetrapropenyl) derivs., calcium salts	
	Based on available data, the classification criteria are not met
C20-24-branched alkyl derivs., calcium	
salts	

Bioaccumulative Potential:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Reaction mass of isomers of: C7-9-alkyl	No test data available
3-(3,5-di-tert-butyl-4-	
hydroxyphenyl)propionate	
Phenol, paraalkylation products with C10-	No test data available
15 branched olefins (C12 rich) derived	
from propene oligomerization, calcium	
salts, sulfurized including distillates	
(petroleum), hydrotreated, solvent-	
refined/dewaxed,cat. dewaxed,	
light/heavy paraffinic C15-C50†	
, , , ,	No test data available
reaction products with carbon dioxide,	
distn. residues from manuf. of phenol	
(tetrapropenyl) derivs. and phenol	
(tetrapropenyl) derivs., calcium salts	
	Based on available data, the classification criteria are not met
C20-24-branched alkyl derivs., calcium	
salts	

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health

Revision Number: 7 13 of 15 HDAX 9200 Low Ash Gas Engine Oil

 Revision Date: October 28, 2024
 SAE 40

 SDS: 37732

authorities for approved disposal or recycling methods. In accordance with European Waste Catalogue (E.W.C.) the codification is the following: 13 02 05

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional description requirements (e.g., technical name) and mode-specific or quantityspecific shipping requirements.

ADR/RID

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN Number or ID Number: Not applicable 14.2 UN proper shipping name: Not applicable 14.3 Transport hazard class(es): Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable 14.6 Special precautions for user: Not applicable

ICAO / IATA

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN Number or ID Number: Not applicable 14.2 UN proper shipping name: Not applicable 14.3 Transport hazard class(es): Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable 14.6 Special precautions for user: Not applicable

IMO / IMDG

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN Number or ID Number: Not applicable **14.2 UN proper shipping name:** Not applicable 14.3 Transport hazard class(es): Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable 14.6 Special precautions for user: Not applicable

14.7 Maritime Transport in Bulk according to IMO Instruments: Not applicable

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **REGULATORY LISTS SEARCHED:**

01=EU Directive 76/769/EEC: Restrictions on the marketing and use of certain dangerous substances. 02=EU Directive 90/394/EEC: Carcinogens at work.

03=EU Directive 92/85/EEC: Pregnant or breastfeeding workers.

04=EU Directive 2012/18/EU: Seveso III.

05=EU Directive 98/24/EC: Chemical agents at work.

06=EU Directive 2004/37/EC: On the protection of workers.

07=EU Regulation EC No. 689/2008: Annex 1, Part 1.

08=EU Regulation EC No. 689/2008: Annex 1, Part 2.

09=EU Regulation EC No. 689/2008: Annex 1, Part 3.

10=EU Regulation EC No. 850/2004: Prohibiting and restricting persistent organic pollutants (POPs).

11=EU REACH, Annex XVII: Restrictions on manufacture, placing on the market and use of certain dangerous substances, mixture & article.

14 of 15

Revision Date: October 28, 2024

Revision Number: 7

HDAX 9200 Low Ash Gas Engine Oil SAE 40

12=EU REACH, Annex XIV: Authorization List or Candidate List of Substances of Very High Concern for Authorization (SVHC).

The following components of this material are found on the regulatory lists indicated. Reaction mass of isomers of: C7-9-alkyl 3-(3,5-ditert-butyl-4-hydroxyphenyl)propionate

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AIIC (Australia), DSL (Canada), ENCS (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States).

One or more components is listed on ELINCS (European Union). All other components are listed or exempted from listing on EINECS.

15.2 Chemical safety assessment

No chemical safety assessment.

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: SECTION 02 - Supplemental Hazard information was modified.

SECTION 06 - Personal Precautions, Protective Equipment and Emergency Procedures information was

SECTION 08 - Respiratory Protection information was added. SECTION 08 - Respiratory Protection information was modified. SECTION 12 - Ecological Information information was modified.

Revision Date: October 28, 2024

Full text of CLP H-statements:

Aguatic Chronic 3/H412; Harmful to aguatic life with long lasting effects Aquatic Chronic 4/H413; May cause long lasting harmful effects to aquatic life Skin Sens. 1/H317; May cause an allergic skin reaction

Skin Irrit. 2/H315; Causes skin irritation

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
CVX - Chevron	CAS - Chemical Abstract Service Number
NQ - Not Quantifiable	

Prepared according to the UK REACH by Chevron.

The information in this SDS is based on the knowledge, information, and belief of Chevron and its affiliates as of the publication date. It is not a quality specification, and no warranty, express or implied, is given. We assume no responsibility or liability for the results of using this material. The information presented here pertains only to the listed product. Since conditions of use are beyond our control, it is the user's responsibility to determine the conditions for safe use of this product and assess its suitability for their application. Users should seek additional guidance if necessary.

No Annex

Revision Number: 7 15 of 15 **HDAX 9200 Low Ash Gas Engine Oil** Revision Date: October 28, 2024 **SAE 40**