# Safety Data Sheet



# **SECTION 1 IDENTIFICATION**

# **Delo Syn-Trans XE SAE 75W-90**

Recommended Use: Manual Transmission Fluid

Restrictions on Use: Consult supplier when used other than those specified.

Product Number(s): 223079

Other means of identification: Not applicable

**Company Identification** Chevron Canada Limited 500 - 5th Ave. SW

Calgary, ALBERTA T2P 0L7

Canada

www.chevronlubricants.com

## **Transportation Emergency Response**

CHEMTREC: (800) 424-9300 or (703) 527-3887

**Health Emergency** 

Chevron Emergency & Information Center: Located in the USA. International collect calls accepted. (800)

231-0623 or (510) 231-0623

**Product Information** 

email: lubemsds@chevron.com Product Information: (800) LUBE TEK

# SECTION 2 HAZARDS IDENTIFICATION

## **CLASSIFICATION:**

- Target organ toxicant (repeated exposure): Category 1.
- Acute aquatic toxicant: Category 2.
- Chronic aquatic toxicant: Category 3.



Signal Word: Danger **Health Hazards:** 

Causes damage to organs (Lymphatic Tissue) through prolonged or repeated exposure (H372).

**Revision Number: 4** 1 of 10 Delo Syn-Trans XE SAE 75W-90

Revision Date: May 13, 2025 **SDS**: 41138

#### **Environmental Hazards:**

- Toxic to aquatic life (H401).
- Harmful to aquatic life with long lasting effects (H412).

## **PRECAUTIONARY STATEMENTS:**

#### Prevention:

- Do not breathe fume, gas, mist, vapours, or spray (P260).
- · Wash thoroughly after handling (P264).
- Do not eat, drink or smoke when using this product (P270).
- Avoid release to the environment (P273).

#### Response:

· Get medical advice or attention if you feel unwell (P314).

#### Disposal:

• Dispose of contents and container in accordance with applicable local, regional, national, and international regulations (P501).

**OTHER HAZARDS:** Not applicable

## **SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS**

COMPONENTS	CAS NUMBER	AMOUNT
Amines, C11-14-branched alkyl, monohexyl and	80939-62-4	1 - 5 %wt/wt
dihexyl phosphates		
Distillates, hydrotreated heavy paraffinic	64742-54-7	1 - 5 %wt/wt
Distillates, solvent-dewaxed heavy paraffinic	64742-65-0	1 - 5 %wt/wt

Note that the actual concentration or concentration range of some or all of the above ingredients is considered confidential business information and is being withheld as permitted by WHMIS 2015.

## SECTION 4 FIRST AID MEASURES

## Description of first aid measures

**Eye:** No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

**Skin:** No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

**Inhalation:** No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

# Most important symptoms and effects, both acute and delayed IMMEDIATE HEALTH EFFECTS

**Eye:** Not expected to cause prolonged or significant eye irritation.

**Skin:** High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first; but, if left untreated, could result in disfigurement or amputation of the affected part.

Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is

Revision Number: 4 2 of 10 Delo Syn-Trans XE SAE 75W-90 Revision Date: May 13, 2025 SDS: 41138

not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

**Ingestion:** Not expected to be harmful if swallowed.

**Inhalation:** Not expected to be harmful if inhaled. Contains a synthetic hydrocarbon oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

#### **DELAYED OR CHRONIC HEALTH EFFECTS:**

**Target Organs:** Contains material that may cause damage to the following organ(s) following repeated exposure: Lymphatic Tissue

## Indication of any immediate medical attention and special treatment needed

**Note to Physicians:** In an accident involving high-pressure equipment, this product may be injected under the skin. Such an accident may result in a small, sometimes bloodless, puncture wound. However, because of its driving force, material injected into a fingertip can be deposited into the palm of the hand. Within 24 hours, there is usually a great deal of swelling, discoloration, and intense throbbing pain. Immediate treatment at a surgical emergency center is recommended.

## **SECTION 5 FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

UNSUITABLE EXTINGUISHING MEDIA: No data available

**Unusual Fire Hazards:** Leaks/ruptures in high pressure system using materials of this type can create a fire hazard when in the vicinity of ignition sources (eg. open flame, pilot lights, sparks, or electric arcs).

## **PROTECTION OF FIRE FIGHTERS:**

**Fire Fighting Instructions:** This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. **Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Nitrogen, Phosphorus.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment and Emergency Procedures:** Observe all relevant local and international regulations. Eliminate all sources of ignition in vicinity of spilled material. Keep out unnecessary and unprotected personnel. Persons entering the contaminated area to correct the problem or to determine whether it is safe to resume normal activities must comply with all instructions and wear appropriate personal protective equipment as indicated in Section 8.

**Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner

Revision Number: 4 3 of 10 Delo Syn-Trans XE SAE 75W-90 Revision Date: May 13, 2025 SDS: 41138

consistent with applicable regulations.

**Reporting:** Report spills to local authorities as appropriate or required.

## **SECTION 7 HANDLING AND STORAGE**

# Precautions for safe handling

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: DO NOT USE IN HIGH PRESSURE SYSTEMS in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed. Keep out of the reach of children. Do not breathe fume, gas, mist, vapours, or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

## **GENERAL CONSIDERATIONS:**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

#### **ENGINEERING CONTROLS:**

Use general ventilation, local exhaust ventilation, or a combination of both.

## PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

Skin Protection: Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon

Delo Syn-Trans XE SAE 75W-90 **Revision Number: 4** 4 of 10 Revision Date: May 13, 2025 **SDS**: 41138

operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and complete facial protection. Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced. Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

Chemical Glove Material	Thickness (mm)	Typical Breakthrough Time (minutes)
Butyl	0.7	15
Neoprene	0.61	7
Nitrile	0.8	7
Polyvinyl Chloride (PVC)	1.1	7
Viton Butyl	0.3	30

Respiratory Protection: A site-specific risk assessment should be conducted by an Occupational Hygienist or a Safety Professional to determine the type and use of respiratory protective equipment. When a site-specific risk assessment determines that respiratory protection is required, use an approved respirator such as:

# Air purifying respirator -

If airborne concentration limits exceed the applicable occupational exposure limit, but are below the maximum use concentration.

Vapors only: organic vapor cartridge (filter type A3 per EN 529:2005).

Vapors and particulates (including generated mists): both an organic vapor cartridge & particulate filter (AP3 filter per EN 529:2005).

Refer to respirator manufacturers to obtain service life of cartridge / filter.

# Positive pressure air-supplying respirator -

If airborne concentration limits exceed the maximum use concentration offered from an air purifying respirator.

Refer to EN 529:2005, USA OSHA 1910.134, and/or other applicable local/regional/national/international standards for regulatory requirements.

# **Occupational Exposure Limits:**

Component	Country/	Form	TWA	STEL	Ceiling	Notation
	Agency					
Distillates, hydrotreated heavy paraffinic	ACGIH		5 mg/m3	10 mg/m3		-
Distillates, solvent-dewaxed heavy paraffinic	ACGIH	-	5 mg/m3	10 mg/m3		-
Distillates, hydrotreated heavy paraffinic	ACGIH	Inhalable fraction	5 mg/m3			-
Distillates, solvent-dewaxed heavy paraffinic	ACGIH	Inhalable fraction	5 mg/m3			

NOTE ON OCCUPATIONAL EXPOSURE LIMITS: Consult local authorities for acceptable provincial values in Canada. Consult the Canadian Standards Association Standard Z94.4-2011 Selection, Use and Care of Respirators.

**Revision Number: 4** 5 of 10 Delo Syn-Trans XE SAE 75W-90 Revision Date: May 13, 2025

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

Attention: the data below are typical values and do not constitute a specification.

Color: Amber

Physical State: Liquid Odor: Faint or Mild pH: Not available

Vapor Pressure: Not available

Relative Vapor Density: Not available

Initial Boiling Point / Boiling Range: Not available

Solubility: Not available

Melting Point / Freezing Point: Not available Relative Density: 0.825 - 0.875 @ 15.6°C (60.1°F)

Particle Characteristics: Not applicable Density: 7.09 lb/gal @ 15.6°C (60°F) (Typical)

Kinematic Viscosity: 95.1 mm<sup>2</sup>/s @ 40°C (104°F) (Typical)

Coefficient of Therm. Expansion / °F: Not available

**Decomposition temperature:** Not available

Partition coefficient n-octanol/water (logarithmic value): Not available

**FLAMMABLE PROPERTIES:** 

Flammability (solid, gas): Not Applicable

Flashpoint: (Cleveland Open Cup) 190 °C (374 °F) (Minimum)

Auto-ignition temperature: Not available

Flammability (Explosive) Limits (% by volume in air): Lower: Not available Upper: Not available

## **SECTION 10 STABILITY AND REACTIVITY**

**Reactivity:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur. May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Incompatibility With Other Materials: Not applicable

Hazardous Decomposition Products: None known (None expected)

Sensitivity to Mechanical Impact: No.

## **SECTION 11 TOXICOLOGICAL INFORMATION**

**Information on Likely Routes of Exposure:** Exposure may occur via ingestion, inhalation, or skin and eye contact.

## Information on toxicological effects

**Serious Eye Damage/Irritation:** The material is not considered an eye irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Revision Number: 4 6 of 10 Delo Syn-Trans XE SAE 75W-90

**Revision Date:** May 13, 2025 **SDS:** 41138

**Skin Corrosion/Irritation:** The material is not considered a skin irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Skin Sensitization:** The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Dermal Toxicity:** The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Oral Toxicity:** The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Inhalation Toxicity:** The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components. For additional information on the acute toxicity of the components, call the technical information center. **Acute Toxicity Estimate:** Not Determined

**Germ Cell Mutagenicity:** The material is not considered a mutagen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Carcinogenicity:** The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Reproductive Toxicity:** The material is not considered a reproductive toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

# **Specific Target Organ Toxicity - Single Exposure:**

The material is not considered a target organ toxicant (single exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Repeated Exposure: This material causes damage to organs through prolonged or repeated exposure. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Aspiration Hazard:** The material is not considered an aspiration hazard.

# Most important symptoms and effects, both acute and delayed IMMEDIATE HEALTH EFFECTS

**Eye:** Not expected to cause prolonged or significant eye irritation.

**Skin:** High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first; but, if left untreated, could result in disfigurement or amputation of the affected part.

Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

**Ingestion:** Not expected to be harmful if swallowed.

**Inhalation:** Not expected to be harmful if inhaled. Contains a synthetic hydrocarbon oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

 Revision Number: 4
 7 of 10
 Delo Syn-Trans XE SAE 75W-90

 Revision Date: May 13, 2025
 SDS: 41138

#### **DELAYED OR CHRONIC HEALTH EFFECTS:**

Target Organs: Contains material that may cause damage to the following organ(s) following repeated exposure: Lymphatic Tissue

## **SECTION 12 ECOLOGICAL INFORMATION**

#### **ECOTOXICITY**

This material is expected to be toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

The product has not been tested. The statement has been derived from the properties of the individual components.

## **MOBILITY**

No data available.

## PERSISTENCE AND DEGRADABILITY

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

#### POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Partition coefficient n-octanol/water (logarithmic value): No data available

## **SECTION 13 DISPOSAL CONSIDERATIONS**

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods. (See B.C. Reg. GY/92 Waste Management Act; R.R.O. 1990, Reg. 347 General-Waste Management; C.C.SM.c. W40 The Waste Reduction and Prevention Act; N.S. Reg. 51/95 and N.S. Reg. 179/96 for examples of Provincial legislation.)

## **SECTION 14 TRANSPORT INFORMATION**

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and modespecific or quantity-specific shipping requirements.

TC Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER TRANSPORT CANADA

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT **UNDER ICAO** 

**DOT Shipping Description:** NOT REGULATED AS HAZARDOUS MATERIAL UNDER 49 CFR

**Revision Number: 4** Delo Syn-Trans XE SAE 75W-90 8 of 10

Revision Date: May 13, 2025 **SDS**: 41138

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:

Not applicable

## **SECTION 15 REGULATORY INFORMATION**

#### REGULATORY LISTS SEARCHED:

01-1=IARC Group 1 01-2A=IARC Group 2A 01-2B=IARC Group 2B

No components of this material were found on the regulatory lists above.

#### **CHEMICAL INVENTORIES:**

All components comply with the following chemical inventory requirements: AIIC (Australia), DSL (Canada), EINECS (European Union), IECSC (China), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States).

One or more components does not comply with the following chemical inventory requirements: ENCS (Japan).

#### **SECTION 16 OTHER INFORMATION**

## **REVISION STATEMENT:**

- SECTION 01 Product Use information was added.
- SECTION 02 Environmental Classification information was modified.
- SECTION 02 Hazard Statements information was added.
- SECTION 02 Hazard Statements information was modified.
- SECTION 02 Health Classification information was added.
- SECTION 02 Other Hazards information was added.
- SECTION 02 Pictogram information was added.
- SECTION 02 Precautionary Statements information was added.
- SECTION 02 Precautionary Statements information was modified.
- SECTION 02 Signal Word information was added.
- SECTION 03 Composition information was modified.
- SECTION 04 Delayed Health Effects Target Organ(s) information was modified.
- SECTION 05 Fire Fighters Protection Measures information was modified.
- SECTION 06 Personal Precautions, Protective Equipment and Emergency Procedures information was modified.
- SECTION 07 Precautionary Measures information was added.
- SECTION 08 Engineering Control Measures information was modified.
- SECTION 08 Occupational Exposure Limit Table information was added.
- SECTION 08 Respiratory Protection information was added.
- SECTION 08 Respiratory Protection information was modified.
- SECTION 08 Skin Protection information was modified.
- SECTION 09 Physical/Chemical Properties information was modified.
- SECTION 11 Specific Target Organ Toxicity Repeated Exposure information was modified.
- SECTION 11 Toxicological Information information was added.
- SECTION 12 Ecological Information information was added.

Revision Number: 4 9 of 10 Delo Syn-Trans XE SAE 75W-90 Revision Date: May 13, 2025 SDS: 41138

SECTION 12 - Ecological Information information was deleted. SECTION 12 - Ecological Information information was modified. SECTION 14 - IMO Classification information was added. SECTION 15 - Chemical Inventories information was modified.

Revision Date: May 13, 2025

## ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

ADDITE HAT MAT HAVE BEEN OUT	D III THIS BOSSINEITT.		
TLV - Threshold Limit Value	TWA - Time Weighted Average		
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit		
GHS - Globally Harmonized System	CAS - Chemical Abstract Service Number		
ACGIH - American Conference of Governmental	IMO/IMDG - International Maritime Dangerous Goods		
Industrial Hygienists	Code		
API - American Petroleum Institute	SDS - Safety Data Sheet		
WHMIS - Workplace Hazardous Materials	NFPA - National Fire Protection Association (USA)		
Information System			
DOT - Department of Transportation (USA)	NTP - National Toxicology Program (USA)		
IARC - International Agency for Research on	OSHA - Occupational Safety and Health Administration		
Cancer			
NCEL - New Chemical Exposure Limit	EPA - Environmental Protection Agency		
SCBA - Self-Contained Breathing Apparatus			

Prepared according to the WHMIS 2015 by Chevron.

The information in this SDS is based on the knowledge, information, and belief of Chevron and its affiliates as of the publication date. It is not a quality specification, and no warranty, express or implied, is given. We assume no responsibility or liability for the results of using this material. The information presented here pertains only to the listed product. Since conditions of use are beyond our control, it is the user's responsibility to determine the conditions for safe use of this product and assess its suitability for their application. Users should seek additional guidance if necessary.

Delo Syn-Trans XE SAE 75W-90 **Revision Number: 4** 10 of 10

Revision Date: May 13, 2025 **SDS**: 41138