# **Safety Data Sheet**



# **SECTION 1 PRODUCT AND COMPANY IDENTIFICATION**

# **Texatherm HT 22**

Product Use: Circulating Oil

**Product Number(s):** 219413, 540509

Company Identification
Chevron Singapore Pte Ltd
3 Fraser Street #12-28
DUO Tower
Singapore 189352

# **Transportation Emergency Response**

Singapore Civil Defense Force: 995

**Health Emergency** 

Chevron Emergency & Information Center: Located in the USA. International collect calls accepted. (800)

231-0623 or (510) 231-0623

**Product Information** 

Product Information: +65-6318-1000 SDS Requests: +65-6318-1000

# **SECTION 2 HAZARDS IDENTIFICATION**

# **CLASSIFICATION:**

Aspiration toxicant: Category 1.



# **Signal Word:** Danger **Health Hazards:**

• May be fatal if swallowed and enters airways (H304).

# PRECAUTIONARY STATEMENTS:

# Response:

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician (P301+P310).
- Do NOT induce vomiting (P331).

# Storage:

· Store locked up (P405).

#### Disposal:

• Dispose of contents/container in accordance with applicable local/regional/national/international regulations (P501).

HAZARDS OTHERWISE NOT CLASSIFIED: Not applicable.

Revision Number: 6 1 of 7 Texatherm HT 22 Revision Date: May 29, 2024 5DS: 41830

## SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Benzene, mono-C10-13-alkyl derivs., distn. residues	84961-70-6	100 %weight

## **SECTION 4 FIRST AID MEASURES**

**Eye:** No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

**Skin:** No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** If swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

**Inhalation:** No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

### **IMMEDIATE HEALTH EFFECTS**

**Eye:** Not expected to cause prolonged or significant eye irritation.

**Skin:** Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

**Ingestion:** Highly toxic; may be fatal if swallowed. Because of its low viscosity, this material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death.

**Inhalation:** Not expected to be harmful if inhaled. Contains a synthetic hydrocarbon oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

**Note to Physicians:** Ingestion of this product or subsequent vomiting may result in aspiration of light hydrocarbon liquid, which may cause pneumonitis.

# **SECTION 5 FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

### PROTECTION OF FIRE FIGHTERS:

**Fire Fighting Instructions:** This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

**Protective Measures:** Eliminate all sources of ignition in vicinity of spilled material. **Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as

 Revision Number: 6
 2 of
 7
 Texatherm HT 22

 Revision Date: May 29, 2024
 SDS: 41830

applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities as appropriate or required.

## **SECTION 7 HANDLING AND STORAGE**

**General Handling Information:** Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Do not taste or swallow. Wash thoroughly after handling.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

## **GENERAL CONSIDERATIONS:**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

## **ENGINEERING CONTROLS:**

Use in a well-ventilated area.

# PERSONAL PROTECTIVE EQUIPMENT

**Eye/Face Protection:** Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

**Skin Protection:** Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and complete facial protection. **Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced.** Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

Chemical Glove Material	Thickness	Typical Breakthrough Time

 Revision Number:
 6
 3 of
 7
 Texatherm HT 22

 Revision Date:
 May 29, 2024
 SDS: 41830

	(mm)	(minutes)
Butyl	0.7	120
Neoprene	0.61	120
Nitrile	0.8	120
Polyvinyl Chloride (PVC)	1.1	120
Viton Butyl	0.3	120

**Respiratory Protection:** No respiratory protection is normally required. If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not

**Occupational Exposure Limits:** No applicable occupational exposure limits exist for this material or its components. Consult local authorities for appropriate values.

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

Attention: the data below are typical values and do not constitute a specification.

Color: Yellow

Physical State: Liquid Odor: Petroleum odor

provide adequate protection.

Odor Threshold: No data available

**pH:** Not Applicable

Vapor Pressure: No data available Relative Vapor Density: No data available

Boiling Point: No data available

**Solubility:** Soluble in hydrocarbon solvents; insoluble in water.

Freezing Point: Not Applicable

Melting Point: No data available

Particle Characteristics: Not applicable

Density: 0.86 kg/l - 0.92 kg/l @ 15°C (59°F)

Kinematic Viscosity: 14 mm2/s @ 40°C (104°F) (Minimum)

Evaporation Rate: No data available

Partition coefficient n-octanol/water (logarithmic value): No data available

# **FLAMMABLE PROPERTIES:**

Flashpoint: (Pensky-Martens Closed Cup) 160 °C (320 °F) (Minimum)

**Autoignition:** 261 °C - 265 °C (502 °F - 509 °F)

Flammability (Explosive) Limits (% by volume in air): Lower: Not Applicable Upper: Not

Applicable

# **SECTION 10 STABILITY AND REACTIVITY**

**Reactivity:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Incompatibility With Other Materials: Not applicable

Hazardous Decomposition Products: None known (None expected) Hazardous Polymerization: Hazardous polymerization will not occur.

## SECTION 11 TOXICOLOGICAL INFORMATION

 Revision Number:
 6
 4 of
 7
 Texatherm HT 22

 Revision Date:
 May 29, 2024
 SDS: 41830

**Eye Irritation:** The material is not considered an eye irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Dermal Toxicity:** The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Skin Irritation:** The material is not considered a skin irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Skin Sensitization:** The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Oral Toxicity:** The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Inhalation Toxicity:** The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Toxicity Estimate: Not Determined

**Germ Cell Mutagenicity:** The material is not considered a mutagen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Carcinogenicity:** The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Reproductive Toxicity:** The material is not considered a reproductive toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Specific Target Organ Toxicity - Single Exposure:** The material is not considered a target organ toxicant (single exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Specific Target Organ Toxicity - Repeated Exposure:** The material is not considered a target organ toxicant (repeated exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Aspiration Hazard:** This material is considered an aspiration hazard based on the kinematic viscosity of the material.

# **SECTION 12 ECOLOGICAL INFORMATION**

## **ECOTOXICITY**

This material is not expected to be harmful to aquatic organisms.

The product has not been tested. The statement has been derived from the properties of the individual components.

#### **MOBILITY**

No data available.

### PERSISTENCE AND DEGRADABILITY

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

 Revision Number: 6
 5 of
 7
 Texatherm HT 22

 Revision Date: May 29, 2024
 SDS: 41830

## POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Partition coefficient n-octanol/water (logarithmic value): No data available

#### Other adverse effects

No other adverse effects identified.

## **SECTION 13 DISPOSAL CONSIDERATIONS**

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

## SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**UN Shipping Description:** NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE UNITED NATIONS MODEL REGULATIONS/RECOMMENDATIONS

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

## SECTION 15 REGULATORY INFORMATION

## **REGULATORY LISTS SEARCHED:**

01-1=IARC Group 1 01-2A=IARC Group 2A 01-2B=IARC Group 2B

No components of this material were found on the regulatory lists above.

# **CHEMICAL INVENTORIES:**

All components comply with the following chemical inventory requirements: EINECS (European Union), IECSC (China), TSCA (United States).

One or more components does not comply with the following chemical inventory requirements: DSL (Canada).

# **SECTION 16 OTHER INFORMATION**

**REVISION STATEMENT:** SECTION 03 - Composition information was modified.

SECTION 08 - Skin Protection information was modified.

SECTION 09 - Physical/Chemical Properties information was added.

SECTION 11 - Carcinogenicity information was added.

SECTION 11 - Germ Cell Mutagenicity information was added.

 Revision Number: 6
 6 of
 7
 Texatherm HT 22

 Revision Date: May 29, 2024
 SDS: 41830

SECTION 11 - Reproductive Toxicity information was added.

SECTION 11 - Specific Target Organ Toxicity - Repeated Exposure information was added. SECTION 11 - Specific Target Organ Toxicity - Single Exposure information was added.

SECTION 11 - Toxicological Information information was added.

SECTION 12 - Ecological Information information was added.

SECTION 12 - Ecological Information information was deleted.

Revision Date: May 29, 2024

# ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
	CAS - Chemical Abstract Service Number
ACGIH - American Conference of Governmental	IMO/IMDG - International Maritime Dangerous Goods
Industrial Hygienists	Code
API - American Petroleum Institute	SDS - Safety Data Sheet
CVX - Chevron	NFPA - National Fire Protection Association (USA)
DOT - Department of Transportation (USA)	NTP - National Toxicology Program (USA)
IARC - International Agency for Research on	OSHA - Occupational Safety and Health Administration
Cancer	

Prepared according to the Singapore Standard SS 586:3 2022

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

**Revision Number:** 6 7 of **Texatherm HT 22** Revision Date: May 29, 2024 **SDS**: 41830