Safety Data Sheet



SECTION 1 IDENTIFICATION

Delo 400 XLE SAE 10W-30

Recommended Use: Heavy Duty Motor Oil

Restrictions on Use: Consult supplier when used other than those specified.

Other means of identification: Delo 400 XLE SAE 10W-30

Product Number(s): 257000, 257011

Company Identification Chevron Products Company a division of Chevron U.S.A. Inc. 5001 Executive Parkway San Ramon, CA 94583 United States of America www.chevronlubricants.com

Transportation Emergency Response

CHEMTREC: (800) 424-9300 or (703) 527-3887

Health Emergency

Chevron Emergency & Information Center: Located in the USA. International collect calls accepted. (800)

231-0623 or (510) 231-0623

Product Information

email: lubemsds@chevron.com

Product Information: 1 (800) 582-3835, LUBETEK@chevron.com

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFICATION:

Not classified as hazardous according to 29 CFR 1910.1200 (2012).

HAZARDS NOT OTHERWISE CLASSIFIED: Not Applicable

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

| COMPONENTS | CAS NUMBER | AMOUNT |
|---|------------|-----------------|
| Distillates, hydrotreated heavy paraffinic | 64742-54-7 | 50 - 90 %weight |
| Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based | 72623-87-1 | 0 - 25 %weight |
| Highly refined mineral oil (C15 - C50) | Mixture | 5 - 15 %weight |

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and

1 of 8 **Revision Number: 8**

Delo 400 XLE SAE 10W-30 Revision Date: October 25, 2024 SDS: 42039

flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Most important symptoms and effects, both acute and delayed **IMMEDIATE HEALTH EFFECTS**

Eve: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

Ingestion: Not expected to be harmful if swallowed.

Inhalation: Not expected to be harmful if inhaled. Contains a synthetic hydrocarbon oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

DELAYED OR OTHER HEALTH EFFECTS: Not classified

Indication of any immediate medical attention and special treatment needed Not Applicable

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

UNSUITABLE EXTINGUISHING MEDIA: No data available

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Nitrogen.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Observe all relevant local and international regulations. Eliminate all sources of ignition in vicinity of spilled material. Keep out unnecessary and unprotected personnel. Persons entering the contaminated area to correct the problem or to determine whether it is safe to resume normal activities must comply with all instructions and wear appropriate personal protective equipment as indicated in Section 8.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner

2 of 8 Delo 400 XLE SAE 10W-30 Revision Number: 8

Revision Date: October 25, 2024 SDS: 42039 consistent with applicable regulations.

Reporting: Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

SECTION 7 HANDLING AND STORAGE

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Keep out of the reach of children.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities. and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

ENGINEERING CONTROLS:

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

Skin Protection: Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and complete facial protection. Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced. Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

| Chemical Glove Material | Thickness | Typical Breakthrough Time |
|--------------------------------|-----------|---------------------------|
| | | |

Delo 400 XLE SAE 10W-30 Revision Number: 8 3 of 8

Revision Date: October 25, 2024 SDS: 42039

| | (mm) | (minutes) |
|-------------|------|-----------|
| Butyl | 0.7 | 120 |
| Nitrile | 0.8 | 240 |
| Viton Butyl | 0.3 | 240 |

Respiratory Protection: A site-specific risk assessment should be conducted by an Occupational Hygienist or a Safety Professional to determine the type and use of respiratory protective equipment. When a site-specific risk assessment determines that respiratory protection is required, use an approved respirator such as:

Air purifying respirator -

If airborne concentration limits exceed the applicable occupational exposure limit, but are below the maximum use concentration.

Vapors only: organic vapor cartridge (filter type A3 per EN 529:2005).

Vapors and particulates (including generated mists): both an organic vapor cartridge & particulate filter (AP3 filter per EN 529:2005).

Refer to respirator manufacturers to obtain service life of cartridge / filter.

Positive pressure air-supplying respirator -

If airborne concentration limits exceed the maximum use concentration offered from an air purifying respirator.

Refer to EN 529:2005, USA OSHA 1910.134, and/or other applicable local/regional/national/international standards for regulatory requirements.

Occupational Exposure Limits:

| Component | Agency | Form | TWA | STEL | Ceiling | Notation |
|---|----------|-----------------------|---------|----------|---------|----------|
| Distillates, hydrotreated heavy paraffinic | ACGIH | | 5 mg/m3 | 10 mg/m3 | | |
| Distillates, hydrotreated heavy paraffinic | ACGIH | Inhalable fraction | 5 mg/m3 | | | |
| Distillates, hydrotreated heavy paraffinic | OSHA Z-1 | - | 5 mg/m3 | | | |
| Distillates, hydrotreated heavy paraffinic | OSHA Z-1 | Mist | 5 mg/m3 | | | |
| Lubricating oils, petroleum, C20- 50, hydrotreated neutral oil- based | ACGIH | Inhalable fraction | 5 mg/m3 | | | |
| Highly refined mineral oil (C15 - C50) | ACGIH | - | 5 mg/m3 | 10 mg/m3 | | |
| Highly refined mineral oil (C15 - C50) | OSHA Z-1 | | 5 mg/m3 | | | |

Consult local authorities for appropriate values.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Amber

Physical State: Liquid Odor: Petroleum odor

Odor Threshold: No data available

pH: Not Applicable

Vapor Pressure: No data available

Revision Number: 8 Delo 400 XLE SAE 10W-30 4 of 8 Revision Date: October 25, 2024

SDS: 42039

Relative Vapor Density: No data available Initial Boiling Point: No data available

Solubility: Soluble in hydrocarbons; insoluble in water

Freezing Point: Not Applicable
Melting Point: No data available
Particle Characteristics: Not applicable
Density: 0.868 kg/l @ 15°C (59°F) (Typical)

Kinematic Viscosity: 11.4 mm2/s @ 100°C (212°F) (Minimum) Coefficient of Therm. Expansion / °F: No data available

Evaporation Rate: No data available

Decomposition temperature: No data available

Partition coefficient n-octanol/water (logarithmic value): No data available

FLAMMABLE PROPERTIES:

Flammability (solid, gas): Not Applicable

Flashpoint: (Cleveland Open Cup) 215 °C (419 °F) (Minimum)

Autoignition: No data available

Flammability (Explosive) Limits (% by volume in air): Lower: Not Applicable Upper: Not

Applicable

SECTION 10 STABILITY AND REACTIVITY

Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur. May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Incompatibility With Other Materials: Not applicable

Hazardous Decomposition Products: None known (None expected)

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Serious Eye Damage/Irritation: The material is not considered an eye irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Skin Corrosion/Irritation: The material is not considered a skin irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Skin Sensitization: The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Dermal Toxicity: The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Oral Toxicity: The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Inhalation Toxicity: The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components. **Acute Toxicity Estimate:** Not Determined

Germ Cell Mutagenicity: The material is not considered a mutagen. The product has not been tested.

Revision Number: 8 5 of 8 Delo 400 XLE SAE 10W-30

Revision Date: October 25, 2024 SDS: 42039

The statement is based on evaluation of data for similar materials or product components.

Carcinogenicity: The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Reproductive Toxicity: The material is not considered a reproductive toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Single Exposure: The material is not considered a target organ toxicant (single exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Repeated Exposure: The material is not considered a target organ toxicant (repeated exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Aspiration Hazard: The material is not considered an aspiration hazard.

ADDITIONAL TOXICOLOGY INFORMATION:

During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY

This material is not expected to be harmful to aquatic organisms.

The product has not been tested. The statement has been derived from the properties of the individual components.

MOBILITY

No data available.

PERSISTENCE AND DEGRADABILITY

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Partition coefficient n-octanol/water (logarithmic value): No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-

Delo 400 XLE SAE 10W-30 Revision Number: 8 6 of 8 SDS: 42039

Revision Date: October 25, 2024

specific or quantity-specific shipping requirements.

DOT Shipping Description: NOT REGULATED AS HAZARDOUS MATERIAL UNDER 49 CFR

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT **UNDER ICAO**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

SECTION 15 REGULATORY INFORMATION

EPCRA 311/312 CATEGORIES: Not applicable

REGULATORY LISTS SEARCHED:

01-1=IARC Group 1 05=MA RTK 01-2A=IARC Group 2A 06=NJ RTK 01-2B=IARC Group 2B 07=PA RTK 02=NTP Carcinogen 08-1=TSCA 5(e) 03=EPCRA 313 08-2=TSCA 12(b)

04=CA Proposition 65

The following components of this material are found on the regulatory lists indicated. Distillates, hydrotreated heavy paraffinic 05, 06, 07

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AIIC (Australia), DSL (Canada), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (United States).

One or more components does not comply with the following chemical inventory requirements: ENCS (Japan), IECSC (China), TCSI (Taiwan).

NEW JERSEY RTK CLASSIFICATION:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Motor oil)

SECTION 16 OTHER INFORMATION

NFPA RATINGS: Health: 0 Flammability: 1 Reactivity: 0

Health: 0 **HMIS RATINGS:** Flammability: 1 Reactivity: 0 (0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation. *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

REVISION STATEMENT:

Revision Number: 8 Delo 400 XLE SAE 10W-30 7 of 8 SDS: 42039

Revision Date: October 25, 2024

- SECTION 01 Company SDS Address information was modified.
- SECTION 01 Product Synonym information was added.
- SECTION 04 Delayed Health Effects Target Organ(s) information was modified.
- SECTION 05 Fire Fighters Protection Measures information was modified.
- SECTION 06 Personal Precautions, Protective Equipment and Emergency Procedures information was modified.
- SECTION 08 Eye/Face Protection information was modified.
- SECTION 08 General Considerations information was modified.
- SECTION 08 Occupational Exposure Limit Table information was modified.
- SECTION 08 Personal Protective Equipment List information was deleted.
- SECTION 08 Personal Protective Equipment information was added.
- SECTION 08 Respiratory Protection information was added.
- SECTION 08 Respiratory Protection information was modified.
- SECTION 08 Skin Protection information was modified.
- SECTION 09 Physical/Chemical Properties information was modified.
- SECTION 11 Carcinogenicity information was added.
- SECTION 11 Germ Cell Mutagenicity information was added.
- SECTION 11 Reproductive Toxicity information was added.
- SECTION 11 Specific Target Organ Toxicity Repeated Exposure information was added.
- SECTION 11 Specific Target Organ Toxicity Single Exposure information was added.
- SECTION 11 Toxicological Information information was added.
- SECTION 11 Toxicological Information information was modified.
- SECTION 15 Regulatory Information information was modified.

Revision Date: October 25, 2024

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

| TLV - Threshold Limit Value | TWA - Time Weighted Average |
|---|--|
| STEL - Short-term Exposure Limit | PEL - Permissible Exposure Limit |
| GHS - Globally Harmonized System | CAS - Chemical Abstract Service Number |
| ACGIH - American Conference of Governmental | IMO/IMDG - International Maritime Dangerous Goods |
| Industrial Hygienists | Code |
| API - American Petroleum Institute | SDS - Safety Data Sheet |
| HMIS - Hazardous Materials Information System | NFPA - National Fire Protection Association (USA) |
| DOT - Department of Transportation (USA) | NTP - National Toxicology Program (USA) |
| IARC - International Agency for Research on | OSHA - Occupational Safety and Health Administration |
| Cancer | |
| NCEL - New Chemical Exposure Limit | EPA - Environmental Protection Agency |
| SCBA - Self-Contained Breathing Apparatus | PNOS - Particles Not Otherwise Specified |

Prepared according to the 29 CFR 1910.1200 (2024) by Chevron.

The information in this SDS is based on the knowledge, information, and belief of Chevron and its affiliates as of the publication date. It is not a quality specification, and no warranty, express or implied, is given. We assume no responsibility or liability for the results of using this material. The information presented here pertains only to the listed product. Since conditions of use are beyond our control, it is the user's responsibility to determine the conditions for safe use of this product and assess its suitability for their application. Users should seek additional guidance if necessary.

Revision Number: 8 8 of 8 Delo 400 XLE SAE 10W-30

Revision Date: October 25, 2024 SDS: 42039