# **Safety Data Sheet**



## SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

# **Delo XLI Corrosion Inhibitor - Premixed**

Product Use: Heavy Duty Coolant Product Number(s): 510585 Company Identification Chevron AlBakri Lubricants Co. Matbouli Plaza, Al Maadi Street Ruwais District, P.O. Box 3757 Jeddah 21481

#### **Transportation Emergency Response**

Transportation Emergency Response Number: +966 50 7500027

## **Health Emergency**

Saudi Arabia

Chevron Emergency & Information Center: Located in the USA. International collect calls accepted. (800) 231-0623 or (510) 231-0623

# **Product Information**

email: info@chevronalbakri.com Product Information: +966 566939490 SDS Requests: +966 566939490

# SECTION 2 HAZARDS IDENTIFICATION

#### **CLASSIFICATION:**

· Reproductive toxicant (developmental): Category 1B.



**Signal Word:** Danger **Health Hazards:** 

· May damage the unborn child (H360D).

## **PRECAUTIONARY STATEMENTS:**

#### **Prevention:**

- Obtain special instructions before use (P201).
- Do not handle until all safety precautions have been read and understood (P202).
- Wear protective gloves/protective clothing/eye protection/face protection (P280).

## Response:

• IF exposed or concerned: Get medical advice/attention (P308+P313).

Storage:

Revision Number: 4 1 of 7 Delo XLI Corrosion Inhibitor - Revision Date: March 03, 2025 Premixed

Store locked up (P405).

#### Disposal:

• Dispose of contents and container in accordance with applicable local, regional, national, and international regulations (P501).

## **SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS**

COMPONENTS	CAS NUMBER	AMOUNT
Sodium 2-ethylhexanoate	19766-89-3	1 - < 3 %weight
Tolyltriazole	29385-43-1	0.1 - < 1 %weight

## SECTION 4 FIRST AID MEASURES

**Eye:** No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

**Skin:** No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

**Inhalation:** No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

#### **IMMEDIATE HEALTH EFFECTS**

**Eye:** Not expected to cause prolonged or significant eye irritation.

**Skin:** Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

**Ingestion:** Not expected to be harmful if swallowed.

Inhalation: Not expected to be harmful if inhaled.

## **DELAYED OR OTHER HEALTH EFFECTS:**

**Reproduction and Birth Defects:** Contains material that may cause harm to the unborn child if swallowed based on animal data. See Section 11 for additional information. Risk depends on duration and level of exposure.

# **SECTION 5 FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

#### PROTECTION OF FIRE FIGHTERS:

**Fire Fighting Instructions:** This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Sodium.

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

Revision Number: 4 2 of 7 Delo XLI Corrosion Inhibitor - Revision Date: March 03, 2025 Premixed

Protective Measures: Observe all relevant local and international regulations. Eliminate all sources of ignition in vicinity of spilled material. Keep out unnecessary and unprotected personnel. Persons entering the contaminated area to correct the problem or to determine whether it is safe to resume normal activities must comply with all instructions in the Exposure Controls/PersonalProtection section. **Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

**Reporting:** Report spills to local authorities as appropriate or required.

## **SECTION 7 HANDLING AND STORAGE**

**Precautionary Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor or fumes. Wash thoroughly after handling. Keep out of the reach of children.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

# SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **GENERAL CONSIDERATIONS:**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

## **ENGINEERING CONTROLS:**

Use general ventilation, local exhaust ventilation, or a combination of both.

## PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

Skin Protection: Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and

**Revision Number: 4** 3 of **Delo XLI Corrosion Inhibitor -**Revision Date: March 03, 2025 Premixed

complete facial protection. Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced. Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

Chemical Glove Material	Thickness (mm)	Typical Breakthrough Time (minutes)
Butyl	0.7	120
Neoprene	0.61	120
Nitrile	0.8	120
Polyvinyl Chloride (PVC)	1.1	120
Viton Butyl	0.3	120

**Respiratory Protection:** Not required for identified conditions of use. A site-specific risk assessment should be conducted by an Occupational Hygienist or a Safety Professional to determine the type and use of respiratory protective equipment. When a site-specific risk assessment determines that respiratory protection is required, use an approved respirator such as:

# Air purifying respirator -

Vapors only: organic vapor cartridge (filter type A3 per EN 529:2005).

Vapors and particulates (including generated mists): both an organic vapor cartridge & particulate filter (AP3 filter per EN 529:2005).

Refer to EN 529:2005, USA OSHA 1910.134, and/or other applicable local/regional/national/international standards for regulatory requirements.

**Occupational Exposure Limits:** No applicable occupational exposure limits exist for this material or its components. Consult local authorities for appropriate values.

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Green

Physical State: Liquid

Odor: Odorless

Odor Threshold: No data available

**pH:** 7.6 - 8.7

Vapor Pressure: No data available Relative Vapor Density: No data available Boiling Point: 100°C (212°F) (Estimated)

**Solubility:** Soluble in water.

Freezing Point: -5°C (23°F) (Typical)
Melting Point: No data available
Particle Characteristics: Not applicable
Density: 1.004 kg/l @ 20°C (68°F) (Typical)
Kinematic Viscosity: No data available

Coefficient of Therm. Expansion / °F: No data available

**Evaporation Rate:** No data available

Partition coefficient n-octanol/water (logarithmic value): No data available

FLAMMABLE PROPERTIES: Flashpoint: Not Applicable

Delo XLI Corrosion Inhibitor -Premixed SDS: 53751

Revision Date: March 03, 2025

**Revision Number: 4** 

**Autoignition:** Not Applicable

Flammability (Explosive) Limits (% by volume in air): Lower: Not Applicable Upper: Not

Applicable

#### SECTION 10 STABILITY AND REACTIVITY

**Reactivity:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides,

etc.

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Incompatibility With Other Materials: Not applicable

**Hazardous Decomposition Products:** None known (None expected) **Hazardous Polymerization:** Hazardous polymerization will not occur.

#### SECTION 11 TOXICOLOGICAL INFORMATION

**Eye Irritation:** The material is not considered an eye irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Dermal Toxicity:** The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components. **Skin Irritation:** The material is not considered a skin irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components. **Skin Sensitization:** The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Oral Toxicity:** The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Inhalation Toxicity:** The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components. **Acute Toxicity Estimate:** Not Determined

**Germ Cell Mutagenicity:** The material is not considered a mutagen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Carcinogenicity:** The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Reproductive Toxicity:** This material may damage the unborn child. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Specific Target Organ Toxicity - Single Exposure:** The material is not considered a target organ toxicant (single exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Specific Target Organ Toxicity - Repeated Exposure:** The material is not considered a target organ toxicant (repeated exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Aspiration Hazard:** The material is not considered an aspiration hazard.

#### ADDITIONAL TOXICOLOGY INFORMATION:

2-Ethylhexanoic acid (2-EXA) caused an increase in liver size and enzyme levels when repeatedly

Revision Number: 4 5 of 7 Delo XLI Corrosion Inhibitor - Revision Date: March 03, 2025 Premixed SDS: 53751

administered to rats via the diet. When administered to pregnant rats by gavage or in drinking water, 2-EXA caused teratogenicity (birth defects) and delayed postnatal development of the pups. Additionally, 2-EXA impaired female fertility in rats. Birth defects were seen in the offspring of mice who were administered sodium 2-ethylhexanoate via intraperitoneal injection during pregnancy.

## **SECTION 12 ECOLOGICAL INFORMATION**

## **ECOTOXICITY**

This material is not expected to be harmful to aquatic organisms.

The product has not been tested. The statement has been derived from the properties of the individual components.

#### **MOBILITY**

No data available.

#### PERSISTENCE AND DEGRADABILITY

This material is expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

## POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Partition coefficient n-octanol/water (logarithmic value): No data available

# **SECTION 13 DISPOSAL CONSIDERATIONS**

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by international, country, or local laws and regulations.

## SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**UN Shipping Description:** NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE UNITED NATIONS MODEL REGULATIONS/RECOMMENDATIONS

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

# SECTION 15 REGULATORY INFORMATION

#### **REGULATORY LISTS SEARCHED:**

01-1=IARC Group 1 01-2A=IARC Group 2A 01-2B=IARC Group 2B

No components of this material were found on the regulatory lists above.

Revision Number: 4 6 of 7 Delo XLI Corrosion Inhibitor - Revision Date: March 03, 2025 Premixed

## **CHEMICAL INVENTORIES:**

All components comply with the following chemical inventory requirements: AIIC (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States).

## **SECTION 16 OTHER INFORMATION**

**REVISION STATEMENT:** SECTION 02 - Precautionary Statements information was modified.

SECTION 06 - Personal Precautions, Protective Equipment and Emergency Procedures information was modified.

SECTION 08 - Respiratory Protection information was added.

SECTION 08 - Respiratory Protection information was deleted.

SECTION 08 - Respiratory Protection information was modified.

SECTION 08 - Skin Protection information was modified.

Revision Date: March 03, 2025

## ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average	
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit	
	CAS - Chemical Abstract Service Number	
ACGIH - American Conference of Governmental	IMO/IMDG - International Maritime Dangerous Goods	
Industrial Hygienists	Code	
API - American Petroleum Institute	SDS - Safety Data Sheet	
CVX - Chevron	NFPA - National Fire Protection Association (USA)	
	NTP - National Toxicology Program (USA)	
IARC - International Agency for Research on Cancer	OSHA - Occupational Safety and Health Administration	

Prepared according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) by Chevron.

The information in this SDS is based on the knowledge, information, and belief of Chevron and its affiliates as of the publication date. It is not a quality specification, and no warranty, express or implied, is given. We assume no responsibility or liability for the results of using this material. The information presented here pertains only to the listed product. Since conditions of use are beyond our control, it is the user's responsibility to determine the conditions for safe use of this product and assess its suitability for their application. Users should seek additional guidance if necessary.

Revision Number: 4 7 of 7 Delo XLI Corrosion Inhibitor

Revision Date: March 03, 2025

Delo XLI Corrosion Inhibitor - Premixed